



# NetVanta 1534 PoE

## Power over Ethernet (PoE), Layer 2 Gigabit Ethernet Switch

### Product Features

- 26-port managed Gigabit Ethernet switch
- 24-Gigabit Ethernet ports and 2 SFP optical ports
- 802.3af and Legacy PoE
- Non-blocking, up to 52 Gbps switching capacity
- 802.1Q tagged and port-based VLANs
- Support for up to 255 active VLANs
- 802.1p and DiffServ prioritization with 4 queues per egress port
- Link aggregation, LLDP and LLDP-MED
- Weighted Round Robin (WRR) and WRR + expedite
- DHCP address management
- RADIUS and TACACS+ authentication
- Port mirroring
- Broadcast, Unicast, and Multicast storm control
- Wi-Fi® access controller for centralized management of NetVanta Wireless Access Points
- Cable diagnostics identifies cable length and detects shorts or open twisted pair
- Familiar CLI and Web GUI
- Limited Lifetime Warranty
- Next Business Day Advance Replacement



The NetVanta® 1534 PoE is a managed, 26-port, Layer 2, Gigabit Ethernet switch designed for fast, secure, cost-effective Local Area Network (LAN) switching. This scalable, full-featured business-class switch is perfect for higher-bandwidth Voice over IP (VoIP) applications needing PoE to power IP Phones, Gigabit-to-the-desktop deployments, robust security concerns and ease of management with an easy-to-use Web-based Graphical User Interface (GUI) and familiar Command Line Interface (CLI).

### Hardware

The NetVanta 1534 PoE rackmount switch provides 26 Gigabit Ethernet ports, consisting of 24 fixed 10/100/1000Base-T Ethernet ports and two Small Form-factor Pluggable (SFP) ports. The 10/100/1000Base-T ports provide auto-rate, auto-duplexing, and auto-MDI/MDI-X sensing. The SFP slots are available to accommodate optical interfaces using industry-standard SFP modules.

### Standards Protocols

Based on the ADTRAN® Operating System (AOS), this device offers support for Link Aggregation (802.3ad); Port Mirroring; and Port-based switching features including Broadcast Storm Control, Spanning Tree (802.1D) and Rapid Spanning Tree (802.1w) for faster network convergence, link redundancy, and recovery from topology changes. Link Layer Discovery Protocol (LLDP) auto-discovers neighboring Ethernet devices, simplifying integration into multi-vendor environments.

### VLANs

All NetVanta switches support 802.1Q trunking and up to 255 port-based VLANs to allow network managers to separate broadcast domains for efficient network performance and traffic control.

### Power over Ethernet

The NetVanta 1534 PoE provides standards-based 802.3af and Legacy PoE functionality for powering IP phones, Wireless Access Points (WAPs), or other devices requiring LAN power.

### Security

Rest assured, with the NetVanta 1534 PoE your network is protected. This product offers a variety of data security features including MAC-based port security, multilevel user passwords, Secure Shell (SSH) and Secure Socket Layer (SSL) for encrypted user login, and Access Authentication and Authorization (AAA) for authentication with RADIUS, RSA SecurID, and TACACS+.

### Quality of Service

NetVanta switches also support QoS to ensure network managers have the ability to prioritize mission-critical traffic like VoIP and control network congestion. The NetVanta 1000 Series offers 802.1p and DiffServ Class of Service (CoS). Each switch supports frame tagging, as well as enforcement of tagged traffic received from trusted sources. Four egress queues (per port) are available for assigning traffic priorities using Weighted Round Robin (WRR).

### Administration

The AOS offers both a CLI that mimics the widely-deployed, industry *de facto* standard and an intuitive Web-based GUI with step-by-step configuration wizards. For centralized enterprise-wide management scheme, ADTRAN offers n-Command®, an intuitive, scalable software suite to manage firmware revisions, push firmware upgrades and configuration changes, backup and restore configurations, and manage security policies and Access Control Lists (ACLs).

NetVanta 1000 Series of Ethernet switches are easily coupled with other ADTRAN products including access routers, Wireless Access Points, IP Business Gateways, IP phones, and VoIP telephony solutions. All of these solutions are backed by ADTRAN's outstanding support and services, and an industry-leading warranty.



**ADTRAN, Inc.**

Attn: Enterprise Networks  
901 Explorer Boulevard  
Huntsville, AL 35806

P.O. Box 140000  
Huntsville, AL 35814-4000

256 963-8000  
256 963-8699 fax

**General Information**

800 9ADTRAN  
info@adtran.com  
www.adtran.com

**Pre-Sales**

**Technical Support**

800 615-1176 toll-free  
application.engineer@adtran.com  
www.adtran.com/support

**Where to Buy**

877 280-8416 toll-free  
channel.sales@adtran.com  
www.adtran.com/where2buy

**Post-Sales**

**Technical Support**

888 423-8726  
support@adtran.com  
www.adtran.com/support

**ACES Installation & Maintenance Service**

888 874-ACES  
aces@adtran.com  
www.adtran.com/support

**International Inquiries**

256 963 8000 voice  
256 963-6300 fax  
international@adtran.com  
www.adtran.com/international

**For the regional office nearest you, visit:**

www.adtran.com/where2buy



ADTRAN is an ISO 9001, ISO 14001, and a TL 9000 certified supplier.

61700591G1-8C July 2009  
Copyright © 2009 ADTRAN, Inc.  
All rights reserved.

# NetVanta<sup>®</sup> 1534 PoE

## Power over Ethernet (PoE), Layer 2 Gigabit Ethernet Switch Product Specifications

### Physical Interface

#### Ethernet Ports

- 24 10/100/1000Base-T
- 2 SFP slots for optical connections
- Auto rate/duplex/MDI/MDI-X

#### Console Port

- DB-9, RS-232

### Switching Performance

- Non-blocking
- 8,000 MAC addresses

### Maximum Forwarding Bandwidth

- 52 Gbps

### Diagnostics

- Port Mirroring
- LLDP (802.1AB)
- LLDP-MED
- Ping
- Cable Diagnostics

### Front Panel Status LEDs

- Power Status
- LAN: Link, Activity, PoE Status

### Port Statistics

- Number of TX/RX Frames
- Number of Collisions
- Number of Errors

### Spanning Tree Support

- 802.1D Spanning Tree
- 802.1w Rapid Spanning Tree

### Link Aggregation

- 802.3ad Link Aggregation
- Support for 6 trunk groups
- Trunk groups consist of up to 8 access ports or 2 uplink ports

### Quality of Service (Qos)

- 802.1p and DiffServ
- 4 output queues per egress port
- Weighted Round Robin (WRR)
- WRR w/expedite queue

### VLAN Support

- Port-based VLANs
- 802.1Q tagged trunked VLANs
- Support for up to 255 active VLANs

### Power Over Ethernet

- 802.3af and Legacy support
- Up to 15.4 W/port
- 370 Total Watts

### Storm Control

- Broadcast, Unicast, and Multicast

### Administration

- Familiar Command Line Interface (CLI)
- Web-based GUI
- n-Command<sup>®</sup> support
- SNMP v3
- SYSLOG Logging
- Email Alerts (SMTP)
- TCL Scripting

### Network Access Control

- Port authentication (802.1x)

### Wi-Fi<sup>®</sup> Controller

- Controls up to 24 NetVanta Wireless Access Points

### Environment

- **Operating Temperature:** 0° to 50 °C (32° to 122 °F)
- **Storage Temperature:** -20° to 70 °C (-4° to 158 °F)
- **Relative Humidity:** Up to 95%, non-condensing

### Physical

- **Chassis:** 1U, 19" rackmountable metal enclosure
- **Dimensions:** 1.7" H, 17.2" W, 12.7" D
- **Weight:** 9.5 lbs.
- **AC Power:** 100–250 VAC, 50/60 Hz
- **Power:** 500 watts

### Agency Approvals

- FCC Part 15 Class A, UL 1950/CSA, CE Mark, C-tick

## Ordering Information

Equipment	Part #
NetVanta 1534 PoE	1700591G1
NetVanta 1000BaseSX SFP (LC Connectors)	1200480E1
NetVanta 1000BaseLX SFP (LC Connectors)	1200481E1



NetVanta 1534 PoE



Back Panel

ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN and NetVanta are registered trademarks of ADTRAN, Inc. and its affiliates in various countries. All other trademarks mentioned in this document are the property of their respective owners. The NetVanta Limited Lifetime Warranty applies to select products. This limited warranty is applicable in all countries where ADTRAN products are sold and where ADTRAN and its authorized service providers offer warranty service. For complete warranty information, visit [www.adtran.com/warranty](http://www.adtran.com/warranty)

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding ADTRAN's export license, please visit [www.adtran.com/exporthicense](http://www.adtran.com/exporthicense)